

Tide Plus



Vanjska jedinica



Daljinski

Prednosti



Super tihi rad



Frost Clean



Inteligentan zrak
(Low wind)



Ugodan san



Funkcija
isušivanja



-15°C grijanje



Wi-Fi kontrola
(hOn)



Produžena
montažna
nožica

Model	Unutarnja		AS25THMHRA-C	AS35TAMHRA-C
	Vanjska		1U25YEFFRA-C	1U35YEFFRA-C
Hlađenje				
Kapacitet	Nominal (Min-Max)	Btu/h	8870(2730-10238)	11920(2730-12286)
	Nominal (Min-Max)	kW	2.6(0.8-3.0)	3.2(0.8-3.6)
Energetska efikasnost	SEER/EER		6.1/3.23	6.1/3.01
Energetski razred			A++	A++
Pdesign kapacitet		kW	2.6	3.2
Snaga električnog priključka	Nominal (Min-Max)	kW	0.8(0.3-1.2)	1.06(0.3-1.6)
Godišnja potrošnja energije		kWh/a	149	184
Temperaturni raspon rada	Min-Max	°C	-10-43°C (out)	-10-43°C (out)
Grijanje				
Kapacitet	Nominal (Min-Max)	Btu/h	9555(2730-10920)	11603(2730-14330)
Kapacitet	Nominal (Min-Max)	kW	2.8(0.8-3.2)	3.4(0.8-4.2)
Energetska efikasnost	SCOP/COP (Mild)		4/3.71	4/3.40
	SCOP (Warm/Cold)		5.1/-	5.1/-
Energetski razred	Mild/Warm/Cold		A+/A+++/-	A+/A+++/-
Pdesign (-10°C)		kW	2.4	2.8
Snaga električnog priključka	Nominal (Min-Max)	kW	0.75(0.3-1.4)	1.0(0.3-1.6)
Godišnja potrošnja energije		kWh/a	840	980
Temperaturni raspon rada		°C	-15-24°C (out)	-15-24°C (out)
Napajanje	Ph/V/Hz		1/220-240/50	1/220-240/50
	Pozicija		Vanjska jedinica	Vanjska jedinica
Unutarnja jedinica				
Neto dimenzije	Š / D / V	mm	820/195/280	820/195/280
Dimenzije sa ambalažom	Š / D / V	mm	909/279/355	909/279/355
Neto/bruto težina		kg	8.2/10.5	8.2/10.5
Protok zraka(Hlađenje/grijanje)	Max	m³/h	500	550
Razina buke - zvučna snaga	Hlađenje (Hi/Mid/Lo/So)	dB(A)	37/33/29/19	38/34/29/20
	Grijanje (Hi/Mid/Lo/So)	dB(A)	37/33/29/19	38/34/29/20
Odvlaživanje		10-3m³/h	1	1.4
Vanjska jedinica				
Neto dimenzije	Š / D / V	mm	700/245/544	700/245/544
Dimenzije sa ambalažom	Š / D / V	mm	845/320/593	845/320/593
Neto/bruto težina		kg	22.8/25.3	23.5/26
Protok zraka(Hlađenje/grijanje)	Max	m³/h	2100	2100
Razina buke - zvučna snaga	Hi	dB(A)	49	50
Radna struja	Max	A	6.2	7.1
Vrsta radne tvari			R32	R32
Količina radne tvari	R32	g	510	530
Promjeri cijevi	Tekućinski	mm	6.35	6.35
	Plinski	mm	9.52	9.52
	Max. dozvoljena duljina	m	20/10	20/10
	Max. duljina cjevovoda bez nadopune	m	5	5
	Nadopuna po dodatnom metru	m/g	20	20

Razmak između nogica - informacije se nalaze u zadnjem dijelu kataloga.