

# Tundra Plus



Vanjska jedinica



Daljinski



Žičani daljinski

## Prednosti



Frost Clean



Inteligentan zrak  
(Low wind)



Ugodan san



Super tihi rad



Wi-Fi kontrola  
(hOn)



-15°C grijanje



On-Off Card

Model		Unutarnja	AS25TAEHRA-THC	AS35TADHRA-THC	AS50TDDHRA-THC	AS68TEDHRA-THC
		Vanjska	1U25YEFFRA-1	1U35MEEFRA-1	1U50MEMFRA-C	1U68RENFRA-C
<b>Hlađenje</b>						
Kapacitet	Nominal (Min-Max)	Btu/h	8870(2730-11600)	12280(3410-13650)	17060(4430-19790)	23880(7500-29000)
	Nominal (Min-Max)	kW	2.6(0.8-3.4)	3.6(1.0-4.0)	5.0(1.3-5.8)	7.0(2.2-8.5)
Energetska efikasnost	SEER/EER		6.2/3.23	6.4/3.23	6.1/3.41	7.1/3.23
Energetski razred			A++	A++	A++	A++
Pdesign kapacitet		kW	2.6	3.6	5.0	7.0
Snaga električnog priključka	Nominal (Min-Max)	kW	0.8(0.3-1.2)	1.11(0.30-1.50)	1.46(0.40-2.00)	2.16(0.70-2.90)
Godišnja potrošnja energije		kWh/a	147	197	287	350
Temperaturni raspon rada	Min-Max	°C	-10-43°C (out)	-10-43°C (out)	-10-43°C (out)	-10-43°C (out)
<b>Grijanje</b>						
Kapacitet	Nominal (Min-Max)	Btu/h	9890(3410-12970)	12620(3750-15690)	17740(4770-20470)	27640(8190-34120)
Kapacitet	Nominal (Min-Max)	kW	2.9(1.0-3.8)	3.7(1.1-4.6)	5.2(1.4-6.0)	8.1(2.4-10.0)
Energetska efikasnost	SCOP/COP (Mild)		4.1/3.71	4.1/3.71	4.0/3.71	4.0/3.71
	SCOP (Warm/Cold)		5.1//	5.1/-	5.1/-	5.1/-
Energetski razred	Mild/Warm/Cold		A+/A+++//	A+/A+++/-	A+/A+++/-	A+/A+++/-
Pdesign (-10°C)		kW	2.4	3.2	4.6	5.6
Snaga električnog priključka	Nominal (Min-Max)	kW	0.78(0.3-1.4)	0.99(0.40-1.50)	1.40(0.52-2.5)	2.18(0.70-2.90)
Godišnja potrošnja energije		kWh/a	819	1092	1610	1963
Temperaturni raspon rada		°C	-15-24°C (out)	-15-24°C (out)	-15-24°C (out)	-15-24°C (out)
Napajanje	Ph/V/Hz		1/230/50	1/230/50	1/230/50	1/230/50
	Pozicija		Vanjska jedinica	Vanjska jedinica	Vanjska jedinica	Vanjska jedinica
<b>Unutarnja jedinica</b>						
Neto dimenzije	Š / D / V	mm	820×195×280	820/195/280	1008/225/318	1125/240/335
Dimenzije sa ambalažom	Š / D / V	mm	909×279×355	909/279/355	1085/329/403	1206/342/418
Neto/bruto težina		kg	8.4/10.5	8.4/10.5	11.6/14.4	14/17.5
Protok zraka(Hlađenje/grijanje)	Max	m³/h	500	550	900	1200
Razina buke - zvučna snaga	Hlađenje (Hi/Mid/Lo/So)	dB(A)	37/32/28/20	38/33/29/21	44/40/35/28	47/43/37/30
	Grijanje (Hi/Mid/Lo/So)	dB(A)	37/32/28/20	38/33/29/21	44/40/35/28	47/43/37/30
Odvlaživanje		10-3m³/h	1.2	1.6	2.0	2.8
<b>Vanjska jedinica</b>						
Neto dimenzije	Š / D / V	mm	700/245/544	800/275/553	800/275/553	890/353/697
Dimenzije sa ambalažom	Š / D / V	mm	845/320/593	908/405/625	908/405/625	1046/460/780
Neto/bruto težina		kg	22.7/25.2	27/30.3	32.7/36.5	47.3/52.3
Protok zraka(Hlađenje/grijanje)	Max	m³/h	2100	2000	2500	2900
Razina buke - zvučna snaga	Hi	dB(A)	47	48	53	52
Radna struja	Max	A	6.2	6.7	11.3	13
Vrsta radne tvari	R32		R32	R32	R32	R32
Količina radne tvari	R32	g	550	620	900	1200
Promjeri cijevi	Tekućinski	mm	6.35	6.35	6.35	6.35
	Plinski	mm	9.52	9.52	12.7	12.7
	Max. dozvoljena duljina	m	20/10	20/10	25/15	25/15
	Max. duljina cjevovoda bez nadopune	m	5	5	7	7
	Nadopuna po dodatnom metru	m/g	20	20	20	20

Razmak između nogica - informacije se nalaze u zadnjem dijelu kataloga.