

Podni inverter model



Super tihi rad
20 dB (A)



Wi-Fi



Dupli ispuh
(gornja i
donja strana)



Jednostavna
instalacija i
održavanje
-podna i zidna
ugradnja



56°C
sterilizacija



Antibakterijski
filter

PODNA JEDINICA			Unutar.	AF25S2SD1FA(H)	AF35S2SD1FA(H)	AF42S2SD1FA(H)
			Vanjska	1U25S2SM1FA-2	1U35S2SM1FA-2	1U42S2SM1FA
HLADNJE	Kapacitet	Nominalno (Min.-Max.)	kW	2,5 (0,8-3,2)	3,4 (1,0-4,0)	4,2 (1,40-4,50)
	Energetska efikasnost / razred	SEER koeficijent	Ušteda energije	8,0 (A++)	7,5 (A++)	7,00 (A++)
	Snaga električnog priključka	Nominalno (Min.-Max.)	kW	0,65 (0,2-1,3)	0,94 (0,3-1,5)	1,30 (0,50-1,60)
	Temperaturni raspon rada (Hlađenje)	Min. - Max.	°C	-20-43°C	-20-43°C	-20-43°C
GRIJANJE	Kapacitet	Nominalno (Min.-Max.)	kW	3,00 (0,80-3,80)	3,5 (1,1-4,5)	4,70 (1,40-5,00)
	Energetska efikasnost / razred	SCOP koeficijent	Ušteda energije	4,2 (A+)	4,2 (A+)	4,0 (A+)
	Snaga električnog priključka - grijanje	Nominalno (Min.-Max.)	kW	0,80 (0,30-1,6)	0,94 (0,5-1,6)	1,50 (0,60-1,90)
	Temperaturni raspon rada (Grijanje)	Min. - Max.	°C	-20-24°C	-20-24°C	-20-24°C
Napajanje		Ph/V/Hz		1/220-240/50/60	1/220-240/50/60	1/220-240/50/60
Napajanje (pozicija)				Vanjska (3x1,5)	Vanjska (3x1,5)	Vanjska (3x1,5)
Unutarnja jedinica						
Neto dimenzije		Š/D/V	mm	700/210/600	700/210/600	700/210/600
Dimenzije sa ambalažom		Š/D/V	mm	783/303/695	783/303/695	783/303/695
Neto / bruto težina			kg	16,5/18,5	16,5/18,5	16,5/18,5
Protok zraka		Max.	m³/h	400/350/300	450/400/350	530/480/430
Ovlaživanje			lit/h	1,2	1,6	1,8
Razina buke - zvučni tlak		(H/Mid/Lo/So)	db(A)	40/32/25/20	42/34/26/21	46/37/33
Vanjska jedinica						
Neto dimenzije		Š/D/V	mm	800/275/553	800/275/553	800/275/553
Dimenzije sa ambalažom		Š/D/V	mm	908/405/625	908/405/625	954/409/625
Neto / bruto težina			kg	27,6/30,4	30/32,9	31,5/34
Protok zraka		Max.	m³/h	1900	2000	2100
Razina buke - zvučni tlak		Hi/Lo	db(A)	47	48	50
Vrsta radne tvari				R32	R32	R32
Količina radne tvari			g	630	780	940
Dodatna količina radne tvari			g/m	20	20	20
Promjeri cijevi	Tekućinski		mm	6,35	6,35	6,35
	Plinski		mm	9,52	9,52	9,52
	Max. dozvoljena duljina cjevovoda		m	20	20	20
	Max. duljina cjevovoda bez nadoknade		m	7	7	7
	Nadoknada po dodatnom metru		g/m	20	20	20
Max. visinska razlika		m	10	10	10	
Međuveza			mm²	4x1,5	4x1,5	4x1,5
Razmak nogica			mm	510	510	510