

Compact CASSETTE



DC fan motor




Fresh air outlet



New panel design
620*620mm



Low sound level



YR-E17A

YR-E16B

YR-HRS01

YR-HQS01

Compact CASSETTE

Model/Indoor unit			AB052MCERA(M)	AB072MCERA(M)	AB092MCERA(M)	AB122MCERA(M)	AB162MCERA(M)	AB182MCERA(M)
Capacity	Cooling	kBtu/h	5.1	7.5	9.5	12.3	15.3	19.1
		kW	1.5	2.2	2.8	3.6	4.5	5.6
Capacity	Heating	kBtu/h	5.8	8.5	10.9	13.6	17.1	21.5
		kW	1.7	2.5	3.2	4	5	6.3
Electrical Parameters	Power supply	Ph/V/Hz	1/220-240/50/60		1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60
	Air flow (H/M/L)	m ³ /h	520/450/400	520/450/400	520/450/400	520/450/400	650/520/450	760/650/520
Performance	Sound pressure level(H/M/L)	dB(A)	32/30/29	32/30/29	32/30/29	33/30/29	33/30/29	34/32/30
	Sound power level(H/M/L)	dB(A)	46/44/43	46/44/43	46/44/43	47/44/43	47/44/43	48/46/44
Installation	External dimensions(W/D/H)	mm	570/570/260	570/570/260	570/570/260	570/570/260	570/570/260	570/570/260
	Shipping dimensions(W/D/H)	mm	718/680/380	718/680/380	718/680/380	718/680/380	718/680/380	718/680/380
	Net/Shipping weight	kg	16/19	16/19	16/19	19/22	19/22	19/22
	Refrigerant liquid pipe	mm	6.35	6.35	6.35	6.35	6.35	6.35
	Refrigerant gas pipe	mm	9.52	9.52	9.52	12.7	12.7	12.7
Panel	Model Name		PB-620KB /PB-620KB(H)	PB-620KB /PB-620KB(H)	PB-620KB /PB-620KB(H)	PB-620KB /PB-620KB(H)	PB-620KB /PB-620KB(H)	PB-620KB /PB-620KB(H)
	External dimensions(W/D/H)	mm	620/620/60	620/620/60	620/620/60	620/620/60	620/620/60	620/620/60
	Shipping dimensions(W/D/H)	mm	660/660/115	660/660/115	660/660/115	660/660/115	660/660/115	660/660/115
Controller	Wired(Optional)	/	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B
		/	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A
	Infrared (Optional)	/	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01
		/	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01

