



Adapter za  
žičani kontroler



Žični  
kontroler  
(opcija)



## ■ PREDNOSTI



### UVC sterilizacija

Emitira UV zrake te na taj način sterilizira zrak koji prolazi kroz klima uređaj s učinkovitošću od 99,9%.



### 56°C sterilizacija

Uništava bakterije i viruse zagrijavanjem isparivača na 56°C u trajanju od 30 minuta.



### ECO senzor

Detektira stanje u prostoru, te ljudsku aktivnost u realnom vremenu, te prilagođava način rada kako bi postigao najbolju energetska učinkovitost i udobnost za korisnike.



Frost Clean



ECO senzor



Jednostavna  
instalacija



Super tihi rad



Wi-Fi kontrola  
(hOn)



I Feel



3D ispuh zraka



Širi prostor  
cijevi

Popis svih funkcija za navedeni model nalazi se na stranicama 32. – 37.

# Flexis Plus

# Haier

2,6 kW

3,5 kW

5,2 kW

7,0 kW

| Model                                                                   |                                     | Unutarnja | AS25S2SF1FA-BH<br>AS25S2SF1FA-S<br>AS25S2SF1FA-WH | AS35S2SF1FA-BH<br>AS35S2SF1FA-S<br>AS35S2SF1FA-WH | AS50S2SF1FA-BH<br>AS50S2SF1FA-WH | AS71S2SF1FA-BH<br>AS71S2SF1FA-WH |
|-------------------------------------------------------------------------|-------------------------------------|-----------|---------------------------------------------------|---------------------------------------------------|----------------------------------|----------------------------------|
|                                                                         |                                     | Vanjska   | 1U25S2SM1FA-2                                     | 1U35S2SM1FA-2                                     | 1U50S2SJ2FA-2                    | 1U71S2ST1FA                      |
| Hlađenje                                                                |                                     |           |                                                   |                                                   |                                  |                                  |
| Kapacitet                                                               | Nominal (Min-Max)                   | Btu/h     | 8870 (2730-10920)                                 | 11940 (3410-13650)                                | 17740 (4770-20470)               | 23890 (7510-25600)               |
|                                                                         | Nominal (Min-Max)                   | kW        | 2.6 (0.8-3.2)                                     | 3.5 (1.0-4.0)                                     | 5.2 (1.4-6.0)                    | 7.0 (2.20-7.70)                  |
| Energetska efikasnost                                                   | SEER/EER                            |           | 8.5/4.00                                          | 8.5/4.00                                          | 7.2/3.60                         | 7.1/3.23                         |
| Energetski razred                                                       |                                     |           | A+++                                              | A+++                                              | A++                              | A++                              |
| Pdesign kapacitet                                                       |                                     | kW        | 2.6                                               | 3.5                                               | 5.2                              | 7.0                              |
| Snaga električnog priključka                                            | Nominal (Min-Max)                   | kW        | 0.65 (0.20-1.20)                                  | 0.87 (0.30-1.50)                                  | 1.4 (0.5-2.0)                    | 2.17 (0.7-2.5)                   |
| Godišnja potrošnja energije                                             |                                     | kWh/a     | 107                                               | 144                                               | 253                              | 345                              |
| Temperaturni raspon rada                                                | Min-Max                             | °C        | -20-43°C (out)                                    | -20-43°C (out)                                    | -20-43°C (out)                   | -20-43°C (out)                   |
| Grijanje                                                                |                                     |           |                                                   |                                                   |                                  |                                  |
| Kapacitet                                                               | Nominal (Min-Max)                   | Btu/h     | 10920 (2730-14330)                                | 14330 (3410-17740)                                | 20470 (4770-23540)               | 27300 (8190-29000)               |
| Kapacitet                                                               | Nominal (Min-Max)                   | kW        | 3.2 (0.8-4.2)                                     | 4.2 (1.0-5.2)                                     | 6.0 (1.4-6.9)                    | 8.0 (2.4-8.5)                    |
| Energetska efikasnost                                                   | SCOP/COP (Mild)                     |           | 4.6/4.00                                          | 4.6/3.81                                          | 4.6/4.00                         | 4.0/3.71                         |
|                                                                         | SCOP (Warm/Cold)                    |           | 5.1/-                                             | 5.1/-                                             | 5.1/3.4                          | 5.1/-                            |
| Energetski razred                                                       | Mild/Warm/Cold                      |           | A++/A+++/-                                        | A++/A+++/-                                        | A++/A+++/A                       | A+/A+++/-                        |
| Pdesign (-10°C)                                                         |                                     | kW        | 2.4                                               | 2.8                                               | 4.6                              | 5.6                              |
| Snaga električnog priključka                                            | Nominal (Min-Max)                   | kW        | 0.8 (0.30-1.50)                                   | 1.1 (0.5-1.6)                                     | 1.5 (0.5-2.35)                   | 2.16 (0.7-2.9)                   |
| Godišnja potrošnja energije                                             |                                     | kWh/a     | 731                                               | 854                                               | 1400                             | 1959                             |
| Temperaturni raspon rada                                                |                                     | °C        | -20-24°C (out)                                    | -20-24°C (out)                                    | -20-24°C (out)                   | -20-24°C (out)                   |
| Napajanje                                                               | Ph/V/Hz                             |           | 1/220-240/50                                      | 1/220-240/50                                      | 1/220-240/50                     | 1/230/50                         |
|                                                                         | Pozicija                            |           | Vanjska jedinica                                  | Vanjska jedinica                                  | Vanjska jedinica                 | Vanjska jedinica                 |
| Unutarnja jedinica                                                      |                                     |           |                                                   |                                                   |                                  |                                  |
| Neto dimenzije                                                          | Š / D / V                           | mm        | 856/197/300                                       | 856/197/300                                       | 999/225/323                      | 1115/235/343                     |
| Dimenzije sa ambalažom                                                  | Š / D / V                           | mm        | 952/283/389                                       | 952/283/389                                       | 1100/314/420                     | 1202/319/432                     |
| Neto/bruto težina                                                       |                                     | kg        | 9.5/12                                            | 9.5/12                                            | 12/15                            | 15.2/18.2                        |
| Protok zraka                                                            | Max                                 | m³/h      | 600                                               | 650                                               | 900                              | 1100                             |
| Razina zvučnog tlaka                                                    | Hlađenje (Hi/Mid/L0/So)             | dB(A)     | 38/32/25/16                                       | 39/33/26/17                                       | 45/41/37/28                      | 47/43/37/33                      |
|                                                                         | Grijanje (Hi/Mid/L0/So)             | dB(A)     | 38/32/25/19                                       | 39/33/26/20                                       | 45/41/37/28                      | 47/43/37/33                      |
| Odvlaživanje                                                            |                                     | 10-3m³/h  | 1.2                                               | 1.6                                               | 2                                | 2.8                              |
| Vanjska jedinica                                                        |                                     |           |                                                   |                                                   |                                  |                                  |
| Neto dimenzije                                                          | Š / D / V                           | mm        | 800/280/553                                       | 800/280/553                                       | 820/306/642                      | 890/340/705                      |
| Dimenzije sa ambalažom                                                  | Š / D / V                           | mm        | 902/375/607                                       | 902/375/607                                       | 940/390/697                      | 1046/460/780                     |
| Neto/bruto težina                                                       |                                     | kg        | 27.6/30.4                                         | 30/32.9                                           | 37.8/40.5                        | 44/48                            |
| Protok zraka                                                            | Max                                 | m³/h      | 1900                                              | 2000                                              | 3000                             | 3600                             |
| Razina zvučnog tlaka                                                    | Hi                                  | dB(A)     | 59                                                | 61                                                | 63                               | 70                               |
| Radna struja                                                            | Max                                 | A         | 6.8                                               | 7.2                                               | 10.7                             | 13                               |
| Vrsta radne tvari                                                       | R32                                 |           | R32                                               | R32                                               | R32                              | R32                              |
| Količina radne tvari                                                    | R32                                 | g         | 630                                               | 780                                               | 1100                             | 1230                             |
| Promjeri cijevi                                                         | Tekućinski                          | mm        | 6.35                                              | 6.35                                              | 6.35                             | 9.52                             |
|                                                                         | Plinski                             | mm        | 9.52                                              | 9.52                                              | 12.7                             | 15.88                            |
|                                                                         | Max. dozvoljena duljina cjevovoda   | m         | 20                                                | 20                                                | 25                               | 25                               |
|                                                                         | Max. visinska razlika               | m         | 10                                                | 0                                                 | 15                               | 15                               |
|                                                                         | Max. duljina cjevovoda bez nadopune | m         | 7                                                 | 7                                                 | 7                                | 7                                |
|                                                                         | Nadopuna po dodatnom metru          | g/m       | 20                                                | 20                                                | 20                               | 45                               |
| Razmak između nogica - informacije se nalaze u zadnjem dijelu kataloga. |                                     |           |                                                   |                                                   |                                  |                                  |