



■ PREDNOSTI



Frost Clean

Smrzava isparivač pomoću vlage iz zraka, te na taj način veže čestice nečistoće i otapanjem ih uklanja kroz odvod kondenzata, dok na ispuhu osigurava čisti zrak.



Super tihi rad

Optimiziran rad ventilatora i motora pruža korisniku potpuni mir i tišinu.



WI-FI kontrola

Preuzimanjem Haier hOn aplikacije na pametni uređaj (Apple ili Android), omogućuje se upravljanje i kontrola klima uređaja s bilo koje lokacije i bilo kada.



Topli start



Frost Clean



Inteligentan zrak



Ugodan san



Funkcija isušivanja



-15°C grijanje



Turbo hlađenje



Produžena montažna nožica

Popis svih funkcija za navedeni model nalazi se na stranicama 32. – 37.

Tide Plus

Model		Unutarnja	AS25THMHRA-C	AS35TAMHRA-C	AS50TDMHRA-C	AS68TDRHRA-C
		Vanjska	1U25YEFFRA-C	1U35YEFFRA-C	1U50MEMFRA-C	1U68WEGFRA-C
Hlađenje						
Kapacitet	Nominal (Min-Max)	Btu/h	8870(2730-10238)	10920(2730-12286)	17060(4430-19790)	23200(7500-29000)
	Nominal (Min-Max)	kW	2.6(0.8-3.0)	3.2(0.8-3.6)	5.0(1.3-5.8)	6.8(2.20-8.50)
Energetska efikasnost	SEER/EER		6.1/3.23	6.1/3.01	6.1/3.41	6.8/3.23
Energetski razred			A++	A++	A++	A++
Pdesign kapacitet		kW	2.6	3.2	5.0	6.8
Snaga električnog priključka	Nominal (Min-Max)	kW	0.8(0.3-1.2)	1.06(0.3-1.6)	1.47(0.40-2.0)	2.10(0.70-2.90)
Godišnja potrošnja energije		kWh/a	149	184	287	350
Temperaturni raspon rada	Min-Max	°C	-10-43°C (out)	-10-43°C (out)	-10-43°C (out)	-15-43°C (out)
Grijanje						
Kapacitet	Nominal (Min-Max)	Btu/h	9555(2730-10920)	11603(2730-14330)	17740(4770-20470)	23200(8180-32410)
Kapacitet	Nominal (Min-Max)	kW	2.8(0.8-3.2)	3.4(0.8-4.2)	5.2(1.4-6.0)	6.8(2.40-9.50)
Energetska efikasnost	SCOP/COP (Mild)		4/3.71	4/3.40	4.0/3.71	4.0/3.71
	SCOP (Warm/Cold)		5.1/-	5.1/-	5.10/-	5.10/-
Energetski razred	Mild/Warm/Cold		A+/A+++/-	A+/A+++/-	A+/A+++/-	A+/A+++/-
Pdesign (-10°C)		kW	2.4	2.8	4.60	5.60
Snaga električnog priključka	Nominal (Min-Max)	kW	0.75(0.3-1.4)	1.0(0.3-1.6)	1.4(0.52-2.50)	1.8(0.60-2.90)
Godišnja potrošnja energije		kWh/a	840	980	1610	1960
Temperaturni raspon rada		°C	-15-24°C (out)	-15-24°C (out)	-15-24°C (out)	-15-24°C (out)
Napajanje	Ph/V/Hz		1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
	Pozicija		Vanjska jedinica	Vanjska jedinica	Vanjska jedinica	Vanjska jedinica
Unutarnja jedinica						
Neto dimenzije	Š / D / V	mm	820/195/280	820/195/280	1008/225/318	1008/225/318
Dimenzije sa ambalažom	Š / D / V	mm	883/269/342	883/269/342	1085/329/403	1085/329/403
Neto/bruto težina		kg	8.2/10.5	8.2/10.5	11.6/14.4	11.6/14.4
Protok zraka	Max	m³/h	500	550	900	1100
Razina zvučnog tlaka	Hlađenje (Hi/Mid/Lo/So)	dB(A)	37/33/29/19	38/34/29/20	44/40/35/28	48/44/38/33
	Grijanje (Hi/Mid/Lo/So)	dB(A)	37/33/29/19	38/34/29/20	44/40/35/28	48/44/38/33
Odvlaživanje		10-3m³/h	1	1.4	2.0	2.8
Vanjska jedinica						
Neto dimenzije	Š / D / V	mm	700/245/544	700/245/544	800/280/553	890/340/705
Dimenzije sa ambalažom	Š / D / V	mm	819/320/592	819/320/592	902/375/614	1010/440/764
Neto/bruto težina		kg	22.8/25.3	23.5/26	32.7/36.5	44/48
Protok zraka	Max	m³/h	2100	2100	2500	2600
Razina zvučnog tlaka	Hi	dB(A)	62	63	65	68
Radna struja	Max	A	6.2	7.1	11.3	13
Vrsta radne tvari	R32		R32	R32	R32	R32
Količina radne tvari	R32	g	510	530	900	1100
Promjeri cijevi	Tekućinski	mm	6.35	6.35	6.35	6.35
	Plinski	mm	9.52	9.52	12.7	12.7
	Max. dozvoljena duljina cjevovoda	m	20	20	25	25
	Max. visinska razlika	m	10	10	15	15
	Max. duljina cjevovoda bez nadopune	m	5	5	7	7
	Nadopuna po dodatnom metru	g/m	20	20	20	20
Razmak između nogica - informacije se nalaze u zadnjem dijelu kataloga.						